

RNASeq Transcriptome Data Analysis Pipeline and Specifications	Document No.:	MCCRD-SOP0012
	Version:	2.0
	Effective Date:	11/01/2017
	Author:	MoCha

1.0 PURPOSE/SCOPE

This Standing Operating Procedure (SOP) describes the pipeline and data analysis specifications for HiSeq RNASeq Pipeline for Patient-Derived Models used/performed by the Molecular Characterization and Clinical Assay Development Laboratory (MoCha) at the Frederick National Laboratory for Cancer Research. **This SOP is for research purposes only and no clinical samples will be processed using this SOP. Any deviation from this SOP will be noted but will not be formally documented.**

2.0 PROCEDURE

- 2.1** FASTQ files are generated with bcl2fastq (version: 2.17.1.14, Illumina). Adaptors are trimmed within this process using the default cutoff of the adapter-stringency option.
- 2.2** PDX Mouse reads are removed from the raw FASTQ files using bbsplit (bbtools v37.36).
- `bbtools bbsplit build=1 -Xmx10g path=<indexPath> in1=Sample.R1.fastq.gz in2=Sample.R2.fastq.gz basename=Sample_%_#.fastq.gz refstats=Sample_stat.txt`
- 2.3** The fastq files are mapped to human transcriptome based on exon models from hg19 using Bowtie2 (version 2.2.6) [1]. The resulting SAM files are converted to BAM format using samtools [2] and the coordinations in BAM are converted to the genomic (hg19) coordinations using RSEM (version 1.2.31). Gene and transcript quantifications are also done using RSEM.
- `rsem-calculate-expression --output-genome-bam --bowtie2 --forward-prob 0 --paired-end Sample_hg19_1.fastq.gz Sample_hg19_2.fastq.gz hg19_UCSC_RefGene_rsem`
- 2.4** Removal of Small nucleolar RNAs (snoRNAs)
- custom script, available upon request

3.0 REFERENCES

1. Langmead B, Salzberg S. Fast gapped-read alignment with Bowtie 2. Nature Methods. 2012, 9:357-359.
2. Li H., Handsaker B., Wysoker A., Fennell T., Ruan J., Homer N., Marth G., Abecasis G., Durbin R. and 1000 Genome Project Data Processing Subgroup (2009) The Sequence alignment/map (SAM) format and SAMtools. Bioinformatics, 25, 2078-9.
3. Li, B. and Dewey, C. N. (2011). RSEM: accurate transcript quantification from RNA-Seq data with or without a reference genome. BMC Bioinformatics. 12:323.
4. Link to BBMap short read aligner on GitHub: <https://github.com/BioInfoTools/BBMap>